

UDC700 Universal Digital Controller and Indicator

Model Selection Guide

Instructions

- Select the desired key number. The arrow to the right marks the selection available.
- Make one selection each from Table I thru VI using the column below the proper arrow. A dot (•) denotes unrestricted availability.

Key Number
DC70_ - I - II - III - IV - V VI

KEY NUMBER	Description	Selection	Availability		
1/32 DIN Controller: Universal Input with Red LED Display	Relay Control Output and SSR Driver Alarm #1	DC701	↓		
	SSR Driver Control Output and Relay Alarm #1	DC702		↓	
	Indicator Only	DC703			↓

TABLE I

Alarm	None	0	•	•	•
	Relay Alarm #2 for Controller or Relay Alarm #1 for Indicator	1	•	•	•
	RS485 Communications (MODBUS protocol)	3	•	•	•

TABLE II

Option 1	Power supply 90 to 240 Vac	0	•	•	•
	Power supply 12 to 30 Vdc/24Vac	1	•	•	•

TABLE III

Display	Red LED Display	0	•	•	•
---------	-----------------	---	---	---	---

TABLE IV

Manuals	English Manuals	0	•	•	•
	Multi-Language Manual	1	•	•	•
	No Manual	2	•	•	•

TABLE V

Packaging	Individually Boxed	0	•	•	•
	Bulk Pack of 10 identical units, 1 manual (if selected in table IV) per pack	1	•	•	•
	Bulk Pack of 100 identical units, individually Boxed, with Manual (if selected in table IV)	2	•	•	•
	Bulk Pack of 100 identical units, 1 Manual per pack (if selected in table IV)	3	•	•	•

TABLE VI

Special	None	0	•	•	•
	Special Instrument Requirement (Consult Factory)	S	•	•	•