

DCP 552 Model Selection Guide

Digital Controller/Programmer (Universal Input/Output Model)

Instructions

- Select the desired Key Number. The arrow to the right marks the selections available.
- Make one selection each from Table I through V, using the column below the proper arrow. A dot (•) denotes unrestricted availability. A letter denotes restricted availability.
- A complete Model Number must have a selection for the Key Number and each table.

Key Number I II III IV V
 [] - [] - [] - [] - [] - []

KEY NUMBER	Description	Selection	Availability
	Two-Channel Digital Controller/Programmer	DCP552	↓

TABLE I

Output	Universal Output	E	•
--------	------------------	---	---

TABLE II

Input Selection	Two Inputs	2	•
-----------------	------------	---	---

TABLE III

Carbon Potential	None	0	•
	Oxygen Sensor Input for Carbon Potential (Note 1)	1	•

TABLE IV

Auxiliary Output	None	0	•
	1 Auxiliary Output	1	•
	2 Auxiliary Outputs and Communication (RS485 or RS232-C)	2	•

TABLE V

Additional Processing	None	00	•
-----------------------	------	----	---

MEMORY CARDSOrder by separate Part Number

Part Number	
Memory Card - 8K	SKM008A-E0
Memory Card - 16K	SKM016A-E0
Memory Card - 64K	SKM064A-E0
Memory Card - 128K	SKM0128A-E0

Note 1: Any Oxygen Sensor made by NGK Insulators, Ltd., Marathon Monitor Co., Cambridge Co., Corning Co., AACC (Advanced Atmosphere Control Corporation) Co., Barber Colman Co., and Furnace Control Co., can be used.

