

STT 3000 Smart Temperature Transmitter Model STT150 and Accessories (Multi-Pack Versions)

Model Selection Guide With Price Data

Model Selection Guide
34-44-16U-05 Issue 6

Key Number

Programmable Temperature Transmitter Module	Order Model Number
Pack of 10 transmitters , each with individual box & installation sheet	
4-20mA output, no galvanic input/output isolation, no hazardous location approvals	STT15RD
4-20mA output, with galvanic isolation, no hazardous location approvals.	STT15UD
4-20mA output, with galvanic isolation and intrinsic safety ⁽¹⁾⁽²⁾	STT15SD
Pack of 20 transmitters , no individual box - single installation sheet.	
4-20mA output, no galvanic input/output isolation, no hazardous location approvals	STT15RM
4-20mA output, with galvanic isolation, no hazardous location approvals.	STT15UM
4-20mA output, with galvanic isolation and intrinsic safety ⁽¹⁾⁽²⁾	STT15SM

- ⁽¹⁾ This includes:
- FM Intrinsic Safety Class I, Div. 1, Groups A, B, C, D
 - FM Non-incendive Class I, Div. 2, Groups A, B, C, D
 - CSA Intrinsic Safety Class I, Div. 1, Groups A, B, C, D
 - INMETRO Flameproof, Zone 1

- ⁽²⁾ IF ATEX intrinsic safety is Required, please specify on order in manufacturing notes section

STT150 Accessories (see also STT 3000 Spare parts Model Selection Guide)

	Part Number
Spring loading mounting kit for STT150 (10 sets)	46188617-502
DIN Rail mounting clip kit for STT150 (10 sets)	46188618-502

Configuration of the STT150 transmitter is with the Smart Configuration Toolkit, SCT 3000 with Table II Option 22 or 33 - in Page : Tools-3 of this Price Book.

Next Page Blank

This page is intentionally left blank.