

## Series 900 Smart Transmitter Replacement Meter Body - R300 In-Line Gage Pressure (LGP)

## Model Selection Guide With Price Data

Model Selection Guide  
34-ST-16U-29 Issue 14

Honeywell Confidential & Proprietary

### Instructions

- These replacement meter bodies are for ST 3000 Release 300 (R300) only.
- Select the desired Key Number per 13-ST-OD-3. The arrow to the right marks the selection available.
- Make one selection from each table, I and II, using the column below the proper arrow. A (♦) denotes unrestricted availability. A letter denotes restricted availability. Restrictions follow Table IV.

Key Number                      I                      II                      III                      IV  
 [ ] - [ ] - [ ] 00 + [ ]

KEY NUMBER	Selection	Availability
<b>Span</b>		
Gage Pressure	0-20 to 0-500 psi/0-1.4 to 0-35 bar STG94LR	↓
	0-300 to 0-3000 psi/0-21 to 0-210 bar STG97LR	↓
	0-500 to 0-6000 psi/0-35 to 0-415 bar STG98LR	↓

TABLE I - METER BODY

Material of Construction	Process Heads	Vent/Drain Valves	Barrier Diaphragms		
	316 St. St.	--	316 LSS	E _ _	♦
	316 St. St.	--	Hastelloy C	F _ _	♦
Fill Fluid	Silicone			_ 1 _	♦
	CTFE			_ 2 _	♦
Process Head Configuration	1/2" NPT (female)			_ _ 0	♦

TABLE II

No Selection	00000	♦
--------------	-------	---

TABLE III - OPTIONS

No Selection	00	♦
--------------	----	---

TABLE IV

Factory Identification	XXXX	♦
------------------------	------	---

*Next Page Blank*

*This page intentionally blank*